

DOCAN

H3220


Resolution
604*2400dpi

Printing Speed
45sqm/h
(Production)

Printing Size
3.2*2.0m




Ricoh Gen6




4Pass(3Row): 54~60sqm/h
6Pass(3Row): 36~45sqm/h
8Pass(3Row): 27~32sqm/h

Konica 1024A



4Pass(2Row): 44~52sqm/h
6Pass(2Row): 36~42sqm/h
8Pass(2Row): 28~35sqm/h

Kyocera




4Pass(1Row): 30sqm/h
6Pass(1Row): 20sqm/h
8Pass(1Row): 17sqm/h

H3220

DOCAN

DURABLE & RELIABLE | HIGH-VALUE UV INKJET FLATBED PRINTER

DEVICE CONFIG _____ ///



3.2x2.0M Printing Area



Ink Tube Cleaning Button



Metal Raster



Sub Tank Heating

EQUIPMENT PARAMETERS _____ ///

Printer Model	H3220					
Print Head Options	Konica 1024A (6PL)		Ricoh Gen6 (5PL)		Kyocera (3.5PL)	
Printing Size	3200x2000mm					
UV Lamp	UV LED Light					
Rip Software	SAI/ONYX/Caldera					
Media Thickness	1-100mm					
Print Head Number	4-12pcs		2-9pcs		2-6pcs	
Ink Color	CMYK/LC/LM+W+V					
Resolution	726*720dpi		726*600dpi		604*1200dpi	
	726*1080dpi		726*900dpi		604*1800dpi	
	726*1440dpi		726*1200dpi		604*2400dpi	
Ink Tank Volume	2L					
Image Format	TIFF, JPEG, EPS, PDF					
Printing Speed	4Pass(2 Row)	44~52sqm/h	54~60sqm/h	4Pass (3 Row)	4Pass (1 Row)	30sqm/h
	6Pass(2 Row)	36~42sqm/h	36~45sqm/h	6Pass (3 Row)	6Pass (1 Row)	20sqm/h
	8Pass(2 Row)	28~35sqm/h	27~32sqm/h	8Pass (3 Row)	8Pass (1 Row)	17sqm/h
Power Supply	AC220V 50/60HZ 10KW 45A					
Environment	Temperature 20-28 °C Humidity 40-60%					
Machine Dimensions	5200*2900*1400mm					
Machine Weight	2180kg					
Outdoor Lifetime	2Year(use DOCAN ink)					
Warranty	One year					

*For detailed information on other available models, please refer to the product brochure.