




Details

- 100% Polyester woven fabric with permanent adhesive
- Block-out function prevents disturbance caused by backside color and this enables to represent stable color
- Has high color density thanks to its semi-matte surface
- 120g paper with PE coating on both sides make the products safe from deformation caused by moisture.

Permanent Adhesion for longtime display on the painted walls, relatively rough surfaces, but depend on wall's condition.

Specifications

Length (m)	30	Width (inch)	50" / 54" / 60"
Weight (g/ m ²)	370	Coating	Resin
Caliper (um)	365	Base Material	Polyester Woven Fabric
Inner Core (inch)	3	Printer	  
Surface	Semi - matte		

KEY FEATURES

- Permanent Adhesive
- 100% Polyester woven fabric
- Has high color density
- Block-out (not 100%, but light block-out)
- Stable with deformation (Liner)

Application

- Label, Stickers, Mural wall coverings, Large retail displays, P.O.P., Custom Wallpapers
- * Available surface :
 - Smooth surface : Glass, SUS
 - Texture surface : Wall paper, Painted wall with low V.O.C

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

Attachment Tip

Get rid of all residue before attachment to keep it from being blistered
Be cautious when attach it to painted surface that paint might peel off
Be cautious about stretching when repositioning the materials.
 Take the possible care for residue not to be left after attach it to slippery surface.
 Use it under fine weather is recommended that adhesion could be up to the weather condition.

Operation Tip

Sprinkling water is needed upon requested situation.
 It needs care to avoid the extension of base when re-attachement.
Use of soft squeezer is required to prevent the scratches on surface.
(* To have better scratch-resistant, recommended to apply liquid coating or spray)

**** TRIAL WITH SAMPLE BEFORE USE IS RECOMMENDED. / YOU CAN CHECK INSTALL CONDITION AFTER 24 HOURS.**
**** Recommended to test on customer's wall prior to use.**

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.



Head office (Korea)
 Natura Media Inc.
 Tel : +82-(0)2-3788-0331
 Fax : +82-(0)2-3788-0326
 sales@naturamedia.co.kr

Europe Branch (Belgium)
 Natura Europe S.A
 Tel : +32-65-321-562
 Fax : +32-65-470-393
 jh.hong@naturamedia.co.kr

Natura Meida USA
 Natura Media USA Inc.
 Tel : +1-470-359-2111
 Fax : +1-470-359-2199
 pkwak@naturamedia.co.kr