


FR3200M



Printer Model	FR3200M			
Print Head Category	Kyocera (3.5PL)	Ricoh Gen5 (7PL)	Ricoh Gen6 (5PL)	Konica 1024a (6PL)
Printing Size	3200mm			
UV Lamp	UV LED light			
Rip Software	Onyx/Caldera	Photoprint/Onyx		
Media Thickness	1-30mm			
Print Head NO.	2-6pcs	2-9pcs	4-10pcs	
Ink Color	CMYK/LC/LM+W	CMYK/LC/LM+W+V		
Resolution	726*1200dpi	//	726*600dpi	479*720dpi
	726*1800dpi	508*900dpi	726*900dpi	479*1080dpi
	726*2400dpi	508*1200dpi	726*1200dpi	479*1440dpi
Ink Tank Volume	2L			
Image Format	TIFF、JPEG、POSTSCRIPT、EPS、PDF			
Printing Speed	4Pass (1 Row) 52sqm/h	//	4Pass (3 Row) 86sqm/h	4Pass (2 Row) 61sqm/h
	6Pass (1 Row) 35sqm/h	6Pass (3 Row) 43sqm/h	6Pass (3 Row) 62sqm/h	6Pass (2 Row) 45sqm/h
	8Pass (1 Row) 26sqm/h	8Pass (3 Row) 30sqm/h	8Pass (3 Row) 43sqm/h	8Pass (2 Row) 31sqm/h
Power Supply	AC 220V,50/60HZ>30A			
Enviroment	Temperature 20-28 °C			
	Humidity 40-60%			
Machine Size	5120*1562*1530mm			
Machine Weight	1650kg			
Outdoor Shelf Life	2Year(use DOCAN ink)			
Warranty Time	One year			

Technical specifications, designs are subject to change without prior notice.

Liner motor




Linear motor driving increasing 10% of carriage moving when acceleration and deceleration.

Stable Movement




Moving belt for y axial material feeding.

User Friendly



Ink level alarm to remind operator to reload ink when ink level low.

Low Vibration



IGUS towline gives smooth moving during speed acceleration & deceleration, well protect inside cables and pipes.

Perfect Curing



High energy LED lamp for better curing on almost all kind of material.

High Precision




X Axial equipped with 1 μm metal raster, gives a high precisely ink drops control. Makes only 1 micro tolerance on Bi-direction printing.

High Capacity




2L main ink tank with auto ink refill reminding system. Max the machine printing capacity and release operator from one machine to more machine operating.

Quiet Movement




Japan THK mute guiderail makes smooth movement and low noise come ture.

Fast Adjustment



According to different printing media, table vacuum force is adjustable.

Convenient Use



Air inflation shaft for flex media feeding and collection.