


H3000M



Printer Model	H3000M			
Print head Category	Ricoh Gen5(7PL)	Ricoh Gen6(5PL)	Kyocera(3.5PL)	Kyocera(3.5PL) (D system)
Printing Size	3200x2000mm			
UV Lamp	UV LED light			
Rip Software	Photoprint/Onyx		Onyx/Caldera	
Media Thickness	1-100mm			
Print Head NO.	2-12pcs		2-10pcs	
Ink Color	CMYK/LC/LM+W+V		CMYK/LC/LM+W	
Resolution	//	726*600dpi	604*1200dpi	
	508*900dpi	726*900dpi	604*1800dpi	
	508*1200dpi	726*1200dpi	604*2400dpi	
Ink Tank Volume	2L			
Image Format	TIFF、JPEG、POSTSCRIPT、EPS、PDF			
Printing Speed	//	4Pass (4 Row) 97sqm/h	4Pass (2 Row) 70sqm/h	High speed (2Row) 117sqm/h
	6Pass (4 Row) 58sqm/h	6Pass (4 Row) 68sqm/h	6Pass (2 Row) 49sqm/h	Production (2Row) 85sqm/h
	8Pass (4 Row) 40sqm/h	8Pass (4 Row) 50sqm/h	8Pass (2 Row) 34sqm/h	Quality (2Row) 47sqm/h
Power Supply	AC 220V,50/60HZ>30A			
Environment	Temperature 20-28 °C			
	Humidity 40-60%			
Machine Size	5570*2930*1505mm			
Machine Weight	2600kg			
Outdoor Shelf Life	2Year(use DOCAN ink)			
Warranty Time	One year			


Technical specifications, designs are subject to change without prior notice.

Maglev Drive



Linear motor driving increasing 10% of carriage moving when acceleration and deceleration.

High Precision



X Axial equipped with 1 μm metal raster, gives a high precisely ink drops control. Makes only 1 micro tolerance on Bi-direction printing.

Quiet Movement



Japan THK mute guiderail makes smooth movement and low noise come ture.

Perfect Curing




High energy LED lamp for better curing on almost all kind of material.

Easy Media unloading



A pedal switch, control reverse air blowing, makes easy media unloading.

Multiple Color Layout



Ricoh G6 Max 12 heads.
Kyocera Max 10 heads.

Strong Power



Two vacuum pump for independent working zone control, enhance the fixation power.

Operation Friendly



Registration pin and ruler for material registration.