FLAT DOT MATTE (ZSO560)

Details

- · Dot adhesive technology, Permanent adhesive, Matte surface PVC Calender.
- · Designed to remove bubbles with high performace without using special liquid mixture.
- · Repositioning available initially, but the adhesive be stronger after positioned.
- · Can be installed by anyone without special techniques because of the dot technology.
- · Eco-solvent, Sovent, UV, Latex ink compatibility

* Condition / Setting

Highly recommend to test this sample roll before you try to target Recommended for indoor usage Clean the mounting object before applying this film

clean the mounting object before applying this fill

Specifications

Standard length (m)	50m	Width (inch)	42", 54" , 60"
Total weight (g/m²)	280g/m² (±10%)	Coating	Resin
Base weight (g/m²)	115g/m² (±10%)	Base Material	PVC
Total caliper (μ)	275μ (±10%)	Printer	
Base caliper (μ)	100μ (±10%)	Peel Strength (SUS, gf/25mm)	Initial 20 min.≥ 100
Surface	Matte		3 days ≥ 450
Inner Core (inch)	3		

KEY FEATURES

- Dot adhesive technology
- Permanent adhesive
- White matte finish
- Easy to install
- Bubbles free

Application

· Architectural window decorations, Glass and Plastic flatness, Window graphics, Trade Show

General Information

- \cdot Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- $\cdot \ Lamination: Optional$
- · Storage : Recommended to strore in closed original packing in a cool 10 $^{\sim}$ 30 $^{\circ}$ C (50 $^{\sim}$ 77 $^{\circ}$ F) and dry environment. (Humidity 35 $^{\sim}$ 65% RH)
- · Shelf Life: 6 month after opening the box (1 year durability)
- * Cautions
- · Recommended to put the blank space when printing the products
- · For outdoor use, recommended to use outdoor lamination film to prevent decoloration.
- · Recommended to use the products after complete or enough drying time
- · Recommended to use double-sided tape or proper finish to prevent detachment from the substrate.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.



 Head office (Korea)
 Europe Branch (Belgium)

 Natura Media Inc.
 Natura Europe S.A

 Tel: +82-(0)2-3788-0331
 Tel: +32-65-321-562

 Fax: +82-(0)2-3788-0326
 Fax: +32-65-470-393

 sales@naturamedia.co.kr
 jh.hong@naturamedia.co.kr

Natura Meida USA
Natura Media USA Inc.
Tel:+1-470-359-2111
Fax:+1-470-359-2199
sales@naturamedia.us