

Larson Bond

CALITATE

IN CIFRE

Evaluation		larson®		ALUCOBOND®		Reynobond®		ALPOLIC®		Asian (Z)	
Alloy	a) 5005: 10 b) 3000 : 8 - 6 c) 1000: 2	5005	10	5005	10	3005	6	3105	6	1100	2
Coating	a) PVdF 70%: 10 b) PVdF 50%: 6 c) PVdF 30%: 2	PVdF 70%	10	PVdF 70%	10	Durogloss HQ Polyester	6	Lumiflon Fluorocarbon	6	PVdF 30% PVdF 40%	2
Protection Film	a) 0-50 µm: 0 b) 50-90 µm: 1 - 3 c) 90-100 µm: 5	100 µm	5	80 µm	3	70 µm	1	70 µm	1	40 µm	0
Internal Face	a) Primer: 5 b) Anodized: 3 c) None: 0	Protection Primer	5	None	0	Protection Primer	5	Protection Primer	5	None	0
Adherence (N/mm ²)	a) <300: 2 b) 300-700: 5 - 7 c) >700: 10	700-900	10	300-400	5	400-600	7	400-500	5	250	2
Core	a) PE Pure/FR >66%<50%: 10 - 4 b) PE Recycled/FR >66%<50%: 6 - 0	PE / FR	10	PE / FR	10	PE / FR	10	PE / FR	10	PE Recycled FR<50%	0
Market Area Quality Level		10		7.6		7		7.6		2	
Europe		7 - 10		North America		6 - 8		East Europe		4 - 7	
South America		4 - 7		Africa		2 - 6		Asia		2 - 6	