



## Details

- Double side coated polyester film for UV and Latex 3rd Generation (Both sides printing available)
- Outstanding expression with bright bluish white color shade
- Great choice of economical solution for UV & LATEX
- Anti-slip treated & Good scratch resistant & Waterproofing
- Matte finish reduces glare and provides high quality image density
- Provides even diffusion of light
- Outstanding Fixation of the UV and Latex ink to the surface

## Specifications

Length (m)	30	Width (inch)	36"/50"/60"
Weight (g/㎡)	255	Coating	Resin
Caliper (μm)	185	Base Material	PET
Inner Core (inch)	3	Printer	 
Surface	Matte		

## KEY FEATURES

- Double side coated PET for both sides printing
- Outstanding expression (Bright bluish white)
- Economical solution for UV & LATEX
- Anti - slip treated
- Anti-scratch & Waterproof
- Even diffusion of light

## Application

- Lightbox advertising, Illuminated displays, Trade show and exhibition graphics & Signage
- Special Backlit application**
  - Cosmetics
  - Fashion image
  - Air Port & great image application

## General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.

### \* Cautions

- Recommended to adjust temperature / humidity when having problem caused by static
- When printing with Latex 300 Series printer, recommended to set proper pass and adjust heating temperature according to ink injection quantity (This is to prevent material's deformation by heat and low drying issue)
- Recommended to test prior to use. If the compatibility with Ink and UV Lam is not suitable, there is risk for lower adhesion.
- Recommended to install with lamination film to prevent blocking issue

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.



Head office (Korea)  
Natura Media Inc.  
Tel : +82-(0)2-3788-0331  
Fax : +82-(0)2-3788-0326  
sales@naturamedia.co.kr

Europe Branch (Belgium)  
Natura Europe S.A  
Tel : +32-65-321-562  
Fax : +32-65-470-393  
jh.hong@naturamedia.co.kr

Natura Meida USA  
Natura Media USA Inc.  
Tel : +1-470-359-2111  
Fax : +1-470-359-2199  
sales@naturamedia.us